



## Paul M. Wolff Co.

Concrete Curing/Hardening • Concrete Floor Staining • Concrete Floor Sealers • Concrete Floor Coatings

Corporate Headquarters: 460 N. Geneva Road • Lindon, UT 84003 • (877) 974-0630 • Fax (801) 785-3547

# ACRI-SHEEN® Floor Sealer

ACRI-SHEEN is a non-yellowing, 30% solids acrylic sealer designed for concrete floors, new and old along with masonry, concrete blocks & bricks. ACRI-SHEEN may be used to seal, harden and dustproof all concrete floors. Won't peel or crack.

### Can be used as:

Hardener...  
Sealer...  
Dustproofer

### DESCRIPTION:

ACRI-SHEEN is an acrylate. It is a transparent sealer and dustproofer. Gives a rich, durable shine, unaffected by ultraviolet light.

### EASY, QUICK APPLICATION

Dries to the touch and may be walked on in less than 2 hours.

### Concrete Surfaces

### STAYS CLEAN

A surface sealed with ACRI-SHEEN ends the constant dusting present on unprotected concrete. ACRI-SHEEN is a good grease proofing and oil proofing surface treatment when properly maintained. Dirt and stains can be mostly removed by simple sweeping and/or scrubbing.

### Aggregate

### Patios

### USE

### Walks

To seal, harden and dustproof concrete floors in manufacturing plants, warehouses, walks and parking garages. Oil proofing for floors, driveways, service station areas and lubrication area. Acid-proofs against most common acids.

### Computer Room

### ECONOMICAL

### Driveways

With ACRI-SHEEN'S low initial cost, ease of application, long life and minimum maintenance coating your floors with ACRI-SHEEN adds up to real economy.

### Chemical Environments

### SURFACE PREPARATION

The surface to be treated must be clean and structurally sound. The extent of surface preparation needed can vary with surface conditions. For new concrete the floor should be scraped, broom cleaned and power scrubbed. Acid etching is not required. Surface cleanliness prior to application is a crucial factor in the appearance of the finished product.

### Laundries

### APPLICATION

### Parking Garage

As a hardener, dustproofer and oil-proofer, on or two coats as recommended. ACRI-SHEEN can be applied at the rate of 400-500 sq. ft. per gallon per coat by spray, mop or lambswool applicator.

### Food Plants

### Dairies

**NOTE:** ACRI-SHEEN is compatible with resilient flooring mastics and alkaline-proof paints.

### Industrial Buildings

### TEST CHARACTERISTICS

Application rate ..... 400-500 sq. ft. (sealing per gal.)

Color ..... Clear

Moisture weight loss ..... @ 350 sq. ft.

Per gal. Passes ASTM ¼ C-309 @

200 sq. ft. per gal. Passes TT-C

00800

Weight per gallon ..... 7.4 lbs.

Chemical resistance ..... after 24 hours

..... Two coats show the following

resistance to 24 hr. exposure of the

following materials:

Acetic Acid 10% ..... No effect

Citric Acid 10% ..... No effect

Ethyl Alcohol (Den) ..... No effect

Hydrochloric Acid 10% ..... No effect

Lemon Juice ..... No effect

Motor Oil ..... No effect

Salt Spray (5% @ 95°F) ..... Exceeds

400 hours

Skydrol 500A & 7000 ..... Film removal

### COMPLIANCES

ACRI-SHEEN meets and exceeds the following specifications:

1. ASTM Designation C-309 Type 1
2. AASHO Designation M-148 Type 1
3. Navy Docks Specification 13 yd.
4. LAAPCD Rule 66.
5. SCAQMD Rule 1113.

### WARNING:

Keep away from heat or flame. Use with adequate ventilation and avoid prolonged breathing of vapors.

For additional information call your PAUL M. WOLFF CO. representative.  
460 North Geneva Road Lindon, UT 84042 (877) 974-0630