



# Paul M. Wolff Co.

Concrete Curing/Hardeing • Concrete Floor Staining • Concrete Floor Sealers • Concrete Floor Coatings

Corporate Headquarters: 460 N. Geneva Road • Lindon, UT 84042 • (877) 974-0630 • Fax (801) 785-3547

# Shur-Seal®

## SHUR-SEAL®

*cures . . .*  
*seals . . .*  
*hardens . . .*  
*dustproofs . . .*

For use on:

Concrete floors

Aggregate

Warehouse floors

Patios

Walks

Driveways

Porches

Chemical  
Environments

Laundries

Garage floors

Damp areas

Food plants

Dairies

Outdoor statuary

Institutions

Industrial plants

**SHUR-SEAL®** is a colorless, transparent, non-flammable, and non-toxic liquid that penetrates concrete floors. This preserves, protects and strengthens concrete floors. **SHUR-SEAL®** may be used to cure, seal, harden, dustproof and alkali-proof concrete floors.

## DESCRIPTION

A colorless, transparent, non-flammable, non-toxic liquid that penetrates concrete floors. SHUR-SEAL® reacts with the moisture and chemical constituents found in concrete to fill the inside spaces of permanent air pockets that are so small that water molecules cannot migrate through. (Commonly known as water glass.)

## USE

To permanently cure, seal, harden, dustproof, and alkali-proof concrete floors and other masonry products.

## ECONOMICAL

SHUR-SEAL® is a permanent treatment that will last for the life of the concrete floors thus the initial cost is the last cost except for normal maintenance.

## SURFACE PREPARATION

For new concrete (less than 120 days old) the floor should be scraped and broom cleaned. The extent of surface preparation needed can vary with surface conditions depending on the presence of other sealers, hardeners and curing agents.

## APPLICATION

Apply with low-pressure spray. For maximum protection apply one coat except on very rough or porous concrete where a second coat may be necessary. After coating has dried there may be slight white deposit on the floor. This will disappear after traffic is allowed in the area.

## TEST CHARACTERISTICS:

Application rate.....	200-300 sq. ft. per gallon
Color.....	Transparent
Oil content .....	None
Wax Content .....	None
Chemical resistance .....	After 24 hrs. The following resistance to 24 hr. exposure of the following material:
Animal Fats .....	No effect
Acetic Acid.....	No effect
Industrial Floor Cleaners .....	No effect
Gasoline .....	No effect
Motor Oil.....	No effect
Brake Fluid.....	No effect
Cutting Oils.....	No effect
Permanent Antifreeze.....	No effect
Vinegar .....	No effect
Phenol .....	No effect
Vegetable Oils .....	No effect
Milk .....	No effect
Lard .....	No effect
Organic Acids.....	No effect
Ketones .....	No effect
Esters .....	No effect
Aliphatic Solvents.....	No effect
Aromatic Solvents .....	No effect

## WARRANTY

Ten Year Application  
Twenty year on material  
Two or more coats only.  
FDA Approved

**Shur-Seal Floor Sealer**

**NOTE:** Unlike surface coatings, which wear away with use, SHUR-SEAL® seals from within the masonry by permanently locking the pores. This process is essentially complete within 90 days but may continue at a much slower rate for up to one year. (*Shur-Seal is not intended for use as a waterproofer.*)

**For More Information Call Your Paul M. Wolff Co. Representative  
(877) 974-0630**